NOTE: THE PREFERRED ARRANGEMENT FOR A SERVICE INSTALLATION IS AN <u>OUTSIDE</u> METER VIEWING CUPBOARD. THIS DRAWING SHOWS AN INTERNAL POSITION ON AN OUTSIDE WALL WHICH IS ACCEPTABLE UNDER CERTAIN CIRCUMSTANCES.
THE LENGTH OF SERVICE CABLE INSIDE ANY BUILDING SHALL NOT EXCEED 2m. MINIMUM OF 750mm ACCESS MUST BE ALLOWED IN FRONT OF METER BOARD. ALL DUCTING TO ES 400 D4. PVC ENTRY DUCT MUST BE RED - WE CANNOT LAY CABLE IN ANY OTHER COLOUR. METERS SHALL BE MOUNTED AT A HEIGHT OF NOT LESS THAN 1m AND NOT MORE THAN 1.35m ABOVE FLOOR LEVEL. INSTALLATION RESPONSIBILITIES ELECTRICITY NORTH WEST LIMITED TO FIT INCOMING CABLE AND METER BOARD CUSTOMER TO FIT ENTRY DUCT SUPPLIER TO FIT METER ENTRY DUCT -FIRST FLOOR LEVEL -100mm WIDTH NEEDED FROM GROUND LEVEL TO FIRST FLOOR FOR CABLE AND CABLE-GUARD INSTALLATION : EXTERNAL ELEVATION (NTS) -750-CLEAR ACCESS **METER** 575 **BOARD** SERVICE CABLE NOT TO EXCEED EXCEED 2m IN LENGTH ENTRY DUCT INSIDE THE BUILDING 32mm Internal Diameter RED PVC DUCT CUSTOMER TO SEAL DUCT 700 FOLLOWING CABLE INSTALLATION 700 FIRST FLOOR 100-200mm LEVEL 7.72 100-200mm

ALL DIMENSIONS MILLIMETERS



TITLE:

SINGLE PHASE SERVICE ARRANGEMENT FOR FIRST FLOOR ENTRY Drawn: JAT

Drawing No:

Date:

10-11-16

SECTION A-A

ENWL-039

Scale: 1:20 @ A4